

Engine Oil**PETRONAS Urania 5000 LSF 5W-30**

Range: PETRONAS Urania 5000

Long description: PETRONAS Urania 5000 LSF 5W-30 is a fully synthetic fuel efficient low SAPS extended drain CK-4/E6 engine oil suitable for Euro VI and Euro V heavy duty diesel applications including modern, high-output, low emission engines fitted with latest emission control systems. It is also suitable for older turbocharged and naturally aspirated diesel engines, both on-highway and off-highway. Suitable for CNG and LNG vehicles where this performance profile is need. It helps in extending engine life and reduces the total cost of ownership. Approved by most important Trucks and Bus manufacturers.

Viscosity: 5W-30

Industry Specifications: API CK-4 ACEA E6, E7, E9

OEM Approvals - Only for Automotive: JASO DH-2 CUMMINS CES 20086 DEUTZ DQC IV-10 LA MACK EOS-4.5 MAN M3677 MB-Approval 228.51 MTU CAT. 3.1 RENAULT RLD-3 VOLVO VDS-4.5

OEM Performance - Only for Automotive: CAT ECF-3 DETROIT DIESEL DFS93K222 DAF Extended Drain

Application(s) - For Consumers pages: Agricultural Equipment, Construction; Quarry & Mining, Heavy-Duty Vehicle (HD)

Sector(s) - For Businesses page: Road Transport