

Coolant



PETRONAS Tutela Coolant Premix

Range:

Long description: High quality ready to use conventional Coolant delivering optimized performance and component durability for heavy-duty engines cooling systems. Formulated with Mono-Ethylene Glycol enhanced with a special Inorganic Acid corrosion inhibitor Technology with nitrites, borates and silicates (IAT Technology), free of phosphates and amines, it provides protection against overheating, frost and corrosion. Suitable for passenger cars, commercial vehicles and off-road machineries where a conventional coolant technology is required.

Industry Specifications: AFNOR NFR 15-601 AS 2108-2004 ASTM D 3306 ASTM D 6210 BS 6580:2010 CUNA 956-16 ONORM V 5123 SAE J1034 SANS 1251:2005 SH 0521-1999

OEM Performance - Only for Automotive: Chrysler MS-9769 CNHi MAT 3620 (IAT) Daimler/Mercedes-Benz 325.0 Fiat 9.55523 IVECO 18-1830 MTU MTL 5048 John Deere JDM H 24 Ford WSS-M97B51-A1

Application(s) - For Consumers pages: Agricultural Equipment, Light-duty Commercial Vehicle (LCV), Passenger car, Construction; Quarry & Mining, Heavy-Duty Vehicle (HD)