

Transmission Fluid



PETRONAS Tutela Multi ATF 700

Range:

Long description: DEXRON®-VI approved, fully synthetic multi-vehicle Automatic Transmission Fluid, Low Viscosity, fuel efficient, long-lasting shifting performance. Suitable for latest generation automatic transmissions, up to 9 speed.

Meets the requirement of Ford MERCON® LV and JASO M315-2013 1A-LV. It is also suitable for use in power steering and hydraulic systems of passenger cars requiring GM DEXRON®-VI/Ford MERCON® LV and previous level of performances.

Suitable for hybrid electrified vehicles

Industry Specifications: Ford MERCON® LV JASO M315-2013 1A-LV JASO M315-2013 1A JASO M315-2013 2A

OEM Approvals - Only for Automotive: GM DEXRON®-VI

OEM Performance - Only for Automotive: JWS 3309, JWS 3314, JWS 3324, JWS 3317 Aisin Warner JWS 3309 (T-IV) & JWS 3324 (WS), AW-1, AW-2 ATF RED 1, RED 1K Audi/Seat/Skoda/VW 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A/30), G 052 025, G 053 025, G 052 162, G 055 025 (JWS 3309), G 052 162, G 055 005, G 055 162, G 060 162, G 052 990, G 055 540, 052 055, VW TL 521 62, VW G 053 001 Bentley PY112995PA BMW JWS 3309 (T-IV), LA2634, LT71141, ZF 5HP18FL/19FL, 5HP24, 5HP30, 7045E, ETL 8072B, BMW MINI, BMW 83 22 0 142 516, ATF 6 Chrysler/Dodge/Jeep ATF+2, +3 (MS 7176E), MOPAR AS 68 RC, AS 69 RC (T-IV), SP IV, NAG1, 05127382AA, 68043742AA, 68171866AA, 68157995AA, 68157995AB, 68218925AA, 68171869AA Daewoo LT 71141 Daihatsu AMMIX ATF D-II, Daihatsu AMMIX ATF D-III SP FIAT 9.55550-AV5, 9.55550-AV3, 9.55550-AV2, 9.55550-AV1, 9.55550-AV6 Ford MERCON®, FF-WSS-M2C-938A/SF, XT-10 QLV, FNR5, XT-9-QMM5, WSS M2C 138CJ, 166H, 922A1, 924A (XT-8-QAW) JWS 3309, XT-2-QDX (M), XT-2-QSM (Syn), ESP-M2C166H, XL-12 Fuso ATF-II, Fuso ATF-SPIII, Fuso ATF-A4 GM 9986195 (Aisin AW, JWS 3309), 1940700, 1940767, 21005966, 22717466, 88900925, 9986195, 93160393, AW1, 88863400, 88863401, Transfer Case (Auto trak II) Hino Blue Ribbon ATF Honda ATF-Z1 (except in CVTs), ATF Ultra II, DW-1, Honda Type 3.0 and Type 3.1 Hyundai/Kia SP-IV, SP-IV M (SP4-M), SPH-IV, SP-IV-RR, SP-III, Dex-II/ SP-II, JWS 3314, NWS 9638 Idemitsu K17 3100 PL085 ISUZU BESCO ATF-II, ATF-III, ATF SP, SCS Fluid, ISUZU 08200-9001 Jaguar ATF 3403 M115, ATF LT71141, ZF 5HP24, ATF 3403 JLM20238, Jaguar K17, JLM 20292, Jaguar Fluid 8432, Jaguar 02JDE26444, WSS-M2C922A1 Land Rover LR023288, TYK500050, LR0022460 Maserati 231603 Mazda ATF D-II, ATF M-III, ATF M-V, ATF FZ, ATF F-1, ATF S-1, ATF N-1, ATF 3317 MINI COOPER T-IV Mitsubishi Diaqueen SK, SP-II, SP-III, SP-IV, AW, J2, J3, ATF PA, ATF MA-1 Nissan Matic Fluid C/D/J/K/S/P Peugeot/Citroen (PSA) ZF 4HP20, Z 000169756, AL4 Automatic gearbox oil (#9730.AE), PSA 16 350 560 80 Porsche ZF 5HP19FL, ZF 5HP20, LT71141, ATF 3403-M115, T-IV (JWS 3309), 000 043 205 09, 999 917 547 00 (A2), 000 043 205 28, Z 000169756 Renault DPO/AL4, Matic D2, Renault Samsung SATF-D Ssang yong DSIH 5M-66 Subaru ATF, ATF SAT, ATF HP, ATF AW-1, AT OIL 5D06, ATF 2326, ATF 2384K Toyota ATF T-IV, ATF WS Volvo 97325, 97335, CE 97340, PN 1161521, PN 1161540/1161640, PN 31256774/31256675, PN 1161621 ZF all 3 & 4 speed, 6 Speed, 8 speed and 9 speed transmissions; ZF TE-ML 05L, 11A, 11B, 21L e-Mobility claims: Toyota THSII Ford Escape Hybrid eCVT Jatco JR712E

Application(s) - For Consumers pages: Light-duty Commercial Vehicle (LCV), Passenger car